



the most experienced
name in high speed
cameras

MEMRECAM HX-3e

High Speed Camera System

The MEMRECAM HX series:
the world's most versatile family of
high speed camera systems!

MEMRECAM HX-3e FEATURES

CMOS Sensor: 2560 X 1920—
all Active Pixels

Bit Depth: 12/10/8-bit
(customer selectable)

Electronic Shutter:
OPEN to 1.1 μ s

Variable Framing Profile:
Test using a variety of frame
rates, sequentially or in parallel.

Versatile Recording: Burst,
multi-trigger, restart-trigger and
image trigger.

A-EST Mode: High resolution
timing and sync system to
< 50 nanoseconds.

Straddle Mode:
Inter-frame time for
PIV applications equals
125 nanoseconds.

Dual Segment Recording:
Simultaneously record to two
distinct memory segments at two
different imaging speeds.

Ultra-High Light Sensitivity

Ruggedized for Range Use



nac's MEMRECAM HX-3e offers an astounding 5 mega Pixel resolution at up to 2,000 fps, Full HD resolution at up to 4,670 fps, 1 Mega Pixel resolution at up to 9,210 fps, and so much more! The HX-3e gives the user the best possible solutions: the highest resolutions available; the highest light sensitivity available; and ultra fast imaging.

The HX-3e is literally two cameras in one!

*When it comes to reliable, high-quality, high-speed camera systems,
make the proven choice with nac and you'll see the visible difference!*

MEMRECAM HX-3e

High Speed Camera System



MEMRECAM HX-3e High Resolution Mode		
Max Res (pixels)	2560 X 1920	
Optical Format	35.20 mm	
fps @ Max Res	2,000	
	Mono	Color
ISO Rating	10,000	2,000

MEMRECAM HX-3e High Speed Mode		
Max Res (pixels)	1280 X 960	
Optical Format	35.20 mm	
fps @ Max Res	7,690	
	Mono	Color
ISO Rating	40,000	8,000

Memory Option	16GB, 32GB, 64GB	
Maximum fps	220,000	

Imaging Formats	Max fps @ Format
High Def: 16 X 9	
1920 X 1080	4,670
1280 X 720	10,230
Other Formats	
4 Mega Pixel	2,400
2 Mega Pixel	4,770
1 Mega Pixel	9,210
XGA (1024 X 768)	11,770
768 X 576	20,180
VGA (640 X 480)	28,310
512 X 512	32,280
512 X 384	42,780
320 X 320	73,660
320 X 240	96,850
320 X 192	119,400
320 X 96	220,000

* Note: Recording Time Depends on Memory Configuration, Resolution, Frame Rate and Image Bit Depth.
 Recording Time (seconds) = [(Memory Configuration X 1024 X 1,000,000) / (Resolution/Frame)] / (Frames/Second)
 Resolution/Frame (Bytes) = (Horizontal pixels X Vertical Pixels X Bit Depth/8)

nac Image Technology

MEMRECAM High Speed Camera Systems also Feature:

- Auto Exposure Control
- Adjustable Frame Rates
- Automatic Temperature Calibration
- Continuously Adjustable Resolution
- Ultra-Fast Gig-E Interface with DataLock
- Fast Download to USB 2.0 HDD
- Continuous Live Video Output
- Remote & Local Control—(no PC required)
- Memory Backup
- DRES—Dynamic Range Expansion Shutter
- Multiple Trigger Modes
- Memory Segmentation
- External Sync Recording
- IRIG-B Capture & Sync with Phase Shift
- Compact, Rugged Design - 6.1kg
120W x 140H x 333D(mm)

Please Note: Specifications described above are preliminary and subject to change.

Visit our website at
www.nacinc.com



Contact Us in the Americas:

nac Image Technology
 193 Jefferson Ave, Suite 102
 Salem, MA 01970 U.S.A.
 Tel: (833) 600-0280
 E-mail: sales@nacinc.com

Contact Us in Europe:

nac Deutschland GmbH
 Hedelfingerstr. 54-70
 70327 Stuttgart, Germany
 Tel: +49(0)711 2201 885
 E-mail: rwestphal@nacinc.de

Contact Us in Asia:

nac Image Technology Inc.
 2-11-3 Kita-Aoyama, Minato-ku
 Tokyo 107-0061 Japan
 Tel: +81 3 3796 7903
 Email: nacinternational@camnac.co.jp